


83 g



[Bi-injection] [Polypropylene - Santoprene™]



>> Type of uses (*)

Thanks to its technical characteristics, this equipment is particularly suitable for all the main works requiring good protection against mechanical risks and projections namely.

Industry. Engineering works. Scouring. Motor industry. Agriculture. Forestry development. Work in a quarry, Joinery work. Maintenance of parks and gardens. Laboratories...

>> Technical features

✓ Safety goggles. Comfortable curved wide lens.

Bi-material mask:

- A rigid polypropylene side.

- A flexible **Santoprene™** side.

Indirect ventilation. Anti-fog clear lens.

Comfortable nose bridge.

Easy adjustable elastic band.

✓ Lens thickness: 2.00 mm.

✓ Weight: 83 gr.

✓ Packing: - Carton of 100 units.

- Box of 10 units.

- Each goggle packed under individual polybag.



Learn more: www.singer.fr

>> Advantages

- ✓ Dual injected soft frame with pressure free fit tight seal design.
- ✓ Anti-fog clear polycarbonate screen.
- ✓ Large and easy adjustable elastic headband thwarts slippery while worn.
- ✓ Fits over most prescription lenses.
- ✓ Slightly curved model (5 °) for a wide and comfortable field of vision.
- ✓ **ISO 9001** manufacturing ensuring a reliable and durable quality.



SINGER

>> Conformity

This product has been tested according to the following European Standard:

✓ **EN 166: 2001**. Personal eye-protection. Specifications.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II**.

EU type examination certificate (**module B**) issued by **BSI (Netherlands)**. Notified body **n°2797**.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Mechanical protection	Symbol BT	Impact resistant against high speed particles at high temperatures (corresponds to the impact of a steel ball with a diameter of 0.86g launched at 120 m/s).
Optical quality	Symbol 1	Class 1 continuous works (better quality).
Scale number	Symbol 9 Symbol 3	Molten metal and hot solids. Liquids.
Optional requirement	Symbol N	Eyepiece with anti-fog treatment.

Your distributor **SINGER® SAFETY**

SINGER® 
safety